

## BRASS SOLENOID VALVE 90




- Coil size 42 mm
- 2/2 way NC
- Pilot operated
- Steam cleaning
- ED 100%

### Technical data

Min differential working pressure	1 bar	
Body material	Brass Nickel plated	
Seal material	PTFE	
Seat and Tube material	Stainless steel	
Working fluids	Steam	
Electrical connection	6,3 x 0,8 fast-on terminal	
Insulation class	H	
220-230VAC 50-60Hz Approvals: CE; VDE	Power (VA)	20
100-120VAC 60Hz Approvals: CE; UL		
12-24 VDC Approvals: CE	Power (W)	14
Max temperature	Fluids	
	PTFE	+80 °C (Version 230V/50Hz: 120°C)
	180 °C	
		Ambient

### Performance



Pipes	Orifice Ø mm	Flow m3/h	MOPD (bar)		Code
			AC	DC	
G 3/8 or 1/2	8	1.1	10	5	9013 – 9014
G 3/8 or 1/2	12	2.4	10	5	9003 – 9004
G 3/4 or 1	21	6.3	10	5	9015 – 9016
G 1 ¼ or 1 ½	38	20.4	10	5	9017 – 9018
G 2	50	34.8	10	5	9019

### Hydraulic connection

G 3/8 - 1/2  
Series 9013 - 9014



G 3/8 - 1/2  
Series 9003 - 9004




G 3/4 - 1 - 1 1/4 - 1 1/2 - 2  
Series 9015 - 9016 - 9017 - 9018 - 9019




### Availability coil orientation


"A" (STANDARD)



"B"



"C"



"D"

