



## A61 TEST & DRAIN VALVES

- Nominal pressure rated to 20.6 bar (300 PSI)
- Working temperature range of -10 / +120°C (14 / 250°F)
- Approval: UL Listed & FM Approved
- Available in 1", 1 1/4", 1 1/2" and 2" pipe size connections
- Standard thread connection: BSPT
- K Factor K80 (K5.6)
- Brass body with three position ball valve OFF / TEST / DRAIN
- Integral sight glass with acrylic see through windows

PART NUMBER	DESCRIPTION	BOX QTY
Datasheet No 7.03		
RDA61Y005	1" (25mm) A61 Test & Drain Valve c/w 1/2" test orifice (for K80 sprinkler)	1
RDA61Y015	1" (25mm) A61 Test & Drain Valve c/w 17/32" test orifice (for K115 sprinkler)	1
RDA61009	1" (25mm) A61 Test & Drain Valve c/w 3/4" test orifice (for K200 sprinkler)	1
RDA61Y006	1 1/4" (32mm) A61 Test & Drain Valve c/w 1/2" test orifice (for K80 sprinkler)	1
RDA61Y016	1 1/4" (32mm) A61 Test & Drain Valve c/w 17/32" test orifice (for K115 sprinkler)	1
RDA61Y012	1 1/4" (32mm) A61 Test & Drain Valve c/w 5/8" test orifice (for K160 sprinkler)	1
RDA61Y010	1 1/4" (32mm) A61 Test & Drain Valve c/w 3/4" test orifice (for K200 sprinkler)	1
RDA61Y032	2" (50mm) A61 Test & Drain Valve c/w 1/2" test orifice (for K80 sprinkler)	1
RDA61Y033	2" (50mm) A61 Test & Drain Valve c/w 17/32" test orifice (for K115 sprinkler)	1
RDA61Y034	2" (50mm) A61 Test & Drain Valve c/w 5/8" test orifice (for K160 sprinkler)	1
RDA61Y035	2" (50mm) A61 Test & Drain Valve c/w 3/4" test orifice (for K200 sprinkler)	1
RDA61Y036	2" (50mm) A61 Test & Drain Valve c/w 15/16" test orifice (for K240 sprinkler)	1
RDA61Y037	2" (50mm) A61 Test & Drain Valve c/w 1 5/64" test orifice (for K320 sprinkler)	1
RDA61Y038	2" (50mm) A61 Test & Drain Valve c/w 1 9/64" test orifice (for K360 sprinkler)	1

Please note A61 test & drain valves are also available in grooved