

MICROSOL



WALL-MOUNTING CONVECTOR HEATERS

Product specifications:

- 4 models with different powers (600/1000/1500/2000 W).
- Protected against splashes of water (protection class X4), they can be installed in damp environments.
- Room thermostat to maintain the set temperature.
- Also equipped with a “no frost” function that switches the unit on automatically when the temperature drops under 5 °C.
- The resin parts have high mechanical strength even at high temperatures (V0 self extinguishing plastic).




KEY FEATURES

- Totally silent operation (no motor inside) makes it particularly useful when there is no central heating.
- Compact dimensions for installations in cramped areas.
- Easy to install: the electric connections can be made with the unit installed on the wall.
- Luminous controls protected by a lift-up door.
- Stand-by luminous control.







DIMENSIONS



Model	Code	A	B	C	Kg
MICROSOL 600 - V0	70562	463	258	109	2.9
MICROSOL 1000 - V0	70572	573	258	109	3.2
MICROSOL 1500 - V0	70582	723	258	109	3.9
MICROSOL 2000 - V0	70592	863	258	109	4.6

Dimensions (mm)

TECHNICAL DATA

MODEL	Code	V	Hz	Power Setting W	A	Insulation	IP
MICROSOL 600 - V0	70562	230	50	300/600	2.6	 cl.I	X4
MICROSOL 1000 - V0	70572	230	50	500/1000	4.3	 cl.I	X4
MICROSOL 1500 - V0	70582	230	50	500/1000/1500	6.5	 cl.I	X4
MICROSOL 2000 - V0	70592	230	50	800/1200/2000	8.7	 cl.I	X4

APPLICATIONS

